



## Solventli Laminasyon

Uses Application	High Retort (135°C)	Semi Retort (under 121°C)	Boil (under 98°C)	Others
<b>Aluminum Construction for food packaging (Curry, pasta sauce, rice porridge, tuna)</b>				
PET/AL/BOPA/ CPP	TM-250HV	TM-250HV		
PET/BOPA/AL/ CPP		TM-219		
PET/AL/ CPP	TM-250HV	TM-250HV		
		TM-219		
<b>Film construction for food packaging (Hamburger steak, shumai dumpling, cooked beans)</b>				
VMPET/(BOPA)/CPP		TM-250HV		
BOPA/ CPP		TM-570		
PET/ CPP			TM-570	
BOPA/LLDPE			TM-219	
<b>Liquid pouch (Soup, frozen food, noodles)</b>				
BOPA/LLDPE			TM-570 TM-219	
KBOPA/LLDPE				
BOPA/(BOPP)/VMPET				
<b>Aluminum construction for general use (Lids)</b>				
PET/AL				TM-340 TM-219
PET/AL/LLDPE				
PET/(BOPA)/VMPET				
<b>Dry foods (Snack foods, rice crackers, candy, pet foods)</b>				
BOPP/ CPP				TM-340 TM-219
BOPP/VMCPP				
BOPP/VMBOPP				
BOPP/Paper				
<b>Non food applications</b>				
PET/AL/LLDPE				TM-570
PET/AL/ CPP				TM-219
PET/AL/BOPA/LLDPE				TM-340
BOPA/LLDPE				